

# Bona Domo

A STEP AHEAD FOR DOMESTIC FLOOR FINISHES





bona.com/domo





#### APPLICATION

Apply the finish using a Bona Polyester Roller. Roll with a smooth flowing motion, alternately across and along the grain of the wood. Apply evenly over the entire surface. Always maintain a "wet edge" to avoid overlaps and allow to dry before applying another layer of finish. Anticipate a slightly longer drying time for each layer that is applied.

### **KEY** BENEFITS

- Good build
- Forgiving/easy application
- Easy to abrade
- Non-yellowing formula
- Primer and topcoat in one

#### TECHNICAL DATA

Type of finish:	Waterborne 1-component polyurethane/acrylate mix
Solids content:	28%



# Bona Domo

### A STEP AHEAD FOR DOMESTIC FINISHES

Bona Domo is a member of the Bona family of premium finishes. With good build and a quick drying formula, it protects the wooden floor in no time. Bona Domo can be used from start to finish, both as a base- and topcoat and is easy to abrade.

Easy and forgiving to apply and with a non-yellowing formula, it comprises all essential properties for treating and protecting wooden floors. Waterborne with low VOC, Bona Domo provides a healthy working environment.

#### TECHNICAL DATA (continued)

Sheen (at 60°):	Silkmatt 40%, Matt 18% (approximate values)
Dilution:	If required, dilute with Bona Retarder (4%) for longer open time.
Drying time:	<ul> <li>Ready for sanding/recoating: 1-2 hours*</li> <li>Light use: 24 hours*</li> <li>Full hardness: 7 days*</li> <li>*under normal climate conditions, 20°C/60% R.H.</li> </ul>
Application tools:	Bona Polyester Roller
Application rate:	8-10 m²/litre (120-100g/m²) per coat
Safety:	Unclassified
Cleaning:	Wipe tools free from residual material before cleaning with a minimal amount of water. Dried material can be removed with acetone.
Shelf life:	1 year from date of production in unopened original container.
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack sizes:	3 x 5 litres (44 boxes per pallet)

