

# Create your Desired Effect

## Bona Nordic Tone + Bona Craft Oil Ash

Enhance the unique character of your home with traditional Scandinavian toning treatment and Bona Craft Oil Ash. Follow these steps to create Bona's signature 2-dimensional effect:

1. Using an oil application sleeve or a fine, wide floor brush, apply one even layer of Bona Nordic Tone in the direction of the wood (8–10 m<sup>2</sup>/litre, 120–100 g/m<sup>2</sup>). Overlap wet-on-wet.
2. If more intensity is desired or if the first application is uneven, apply a second layer after 1–2 hours.
3. Allow the final application to dry for 5–10 hours.
4. Gently sand the surface with Bona Scrad Pad, attached under a buffing machine (low rpm). Move the machine quickly and systematically.
5. Vacuum to remove dust.
6. Apply Bona Craft Oil Ash using Bona Wool Pad.
7. After 15–30 minutes, make another pass with more oil until the surface is saturated i.e. until the wood does not absorb any more oil. The number of treatments needed depends on the type of wood but 1–2 treatments are usually enough.
8. If needed, remove excess oil with cotton cloth and allow surface to dry overnight, minimum 12 hours.



Bona Nordic Tone + Bona Craft Oil Ash

### You will need:

- Bona Nordic Tone
- Bona Craft Oil Ash
- Application sleeve / wide floor brush
- Buffing machine
- Bona Scrad Pad
- Vacuum cleaner
- Bona Wool Pad
- Cotton cloth



### Bona Nordic Tone

Bona Nordic Tone helps enhance the unique character of your home with traditional Scandinavian toning treatment. Combined with Bona Craft Oil, which comes in different colours, you can create your desired Bona 2-dimensional effect.



### Bona Craft Oil

With superior wood saturation properties, Bona Craft Oil delivers deep protection against wear, chemicals and moisture. A natural vegetable oil, it has virtually no odour and significantly lowered VOC. This means that it is safe to work with and live on.