

Bona Decor Paint

Technical data sheet

Bona Decor Paint is a waterborne paint with ultra-hide properties, specially developed for hardwood* floors. It covers in 1-2 coats and establishes an excellent background before being sealed with Bona's waterborne lacquer.

- Excellent hiding
- Quick dry
- Easy application

**only colours Dark Grey and Black are recommended on softwood floors due to potential knot stains.*

Technical data

Type of paint:	1-component waterborne polyurethane dispersion
Colours:	White, Light Grey, Dark Grey, Black
VOC:	Max 140 g/litre
Dilution:	Can be diluted with up to 50 vol.% Bona Novia.
Drying time:	2-3 hours at 20°C/60% R.H.
Application tools:	Bona Microfiber Roller with 5 mm pile
Application rate:	12-15 m ² /litre per coat
Safety	Unclassified, see Safety Data Sheet for more information
Cleaning:	Wipe tools free from residual material before cleaning with a minimum of water. Dried material can be removed with acetone.
Shelf life:	2 years from date of production in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size	5 litres

Preparations

Ensure floor is acclimatized to its end-use environment, well sanded and/or brushed, dry and free from sanding dust, oil, wax and other contamination. Allow paint to reach room temperature and stir the container thoroughly before use. Recommended application conditions are 18-25 C and 30-60% relative air humidity. High temperatures and low humidity shorten, low temperatures and high humidity lengthen drying time. **Minimum temperature for use is 13°C.**

Treatment schedule

- 1x Bona Classic*
- 1-2x Bona Decor Paint
- 1-2x Bona Traffic /HD/Natural

*If using black or dark grey paint, the application of primer can be omitted.

Note: It is not recommended to apply more than two full coats per day due to risk of excessive wood swelling.

Application

Finishing



Bona[®]

Bona Decor Paint

Technical data sheet

Finishing



1. If using White or Light Grey Paint. Pre-treat the surface with Bona Classic Primer and let dry. **Do not sand on the primer.** If using Dark Grey or Black paint then this step can be omitted.
2. Apply paint using a Bona Microfiber Roller 5 mm and let dry.
3. Make a light intermediate abrasion to reduce any grain raise using Bona Scrad Pad with 2x grit 150 Bona Scrad Wings or finer. Vacuum or dust wipe.
4. If required, for complete hiding, apply a second coat of paint and let dry.
5. Protect the surface with any gloss level and version of Bona Traffic or Traffic HD. Alternatively, Bona Novia can be used. Apply 1-2 layers depending on the expected level of wear.

Maintenance

Bona Decor Paint should never be used as the final treatment for timber floors.

The information provided is prepared to the best of our current knowledge but makes no claim to be complete. User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. Bona can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt make a preliminary test. User is required to read and understand all information contained on package labels and safety data sheets before using this product.