# Bona DeepClean W

## Technical data sheet

Bona DeepClean W is a concentrated cleaner for thorough deep cleaning of lacquered and oiled wooden floors. The unique formula provides optimal cleaning efficiency and removes stubborn scuff marks without risk of staining the wood. Can be used with scrubber driers and is particularly suited for the Bona PowerScrubber. Can also be used for manual cleaning.

- Powerful cleaning performance
- Reduced pH prevents alkaline staining
- Optimized for Bona PowerScrubber

#### Technical data

Type product: Surfactant solution pH-value: approx. 9 (concentrate)

Dilution: 1:10 – 1:20, parts concentrate to water

Processing tools: Bona PowerScrubber (white or red brushes), scouring pads,

microfiber pads and similar.

Safety: Unclassified, see safety data sheet for more information.

Shelf life: 2 years from the date of production, in unopened original

container

Storage/Transport: The temperature must not fall below +5°C or exceed +25°C

during storage and transport.

Disposal: Wastes and emptied containers should be handled in

accordance with local regulations

Packaging: 6x1 litre, 3x5 litres

### Processing

Remove loose dust/grit using a vacuum cleaner, scissor mop or other dry cleaning method. Bona Remove W can be used in concentrations 1:1 – 1:5. Test on a small area to determine the required concentration to influence the polish. The upper polish layer should be significantly softer and easy to scratch within 5 minutes if the concentration is satisfactory.

## **Application**

- 1. Apply the diluted product to a section of the floor using a mop or spray equipment. Allow the solution approx. 5 minutes to dissolve the polish.
- 2. Scrub the section using a buffing machine equipped with a green pad.
- Immediately remove the dissolved polish with a wet vacuum or the Bona PowerScrubber. Alternatively, a mop and a bucket of clean water can be used
- 4. It may be necessary to re-apply Bona Remove W depending on how thick the build-up of polish is.
- 5. When the entire floor has been treated, clean once more with only pure water. It is important that all traces of Bona Remove W are removed before applying a new layer of maintenance coating such as Bona Shield W.

**Note:** The amount of water applied to the floor must be kept to a minimum. Pay attention to large gaps in the floor, do not allow excessive amounts of cleaning solution to seep into open gaps.

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. Bona can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt make a preliminary test. User is required to read and understand all information contained on package labels and safety data sheets before using this product.





