

BONA
NORDIC TONE

Bona Nordic Tone

Reactive stain

- ✓ For a white-washed effect
- ✓ Inhibits wood yellowing
- ✓ Quick drying
- ✓ Odourless

Light

5L

Effect colouring for wooden floors.
Farbgebung für Holzböden.
Ecran blanc.
Efecto para colorear suelos de madera.
Effektfärgning för trägolv.

Bona[®]

Create **your** own wood **story**

BONA OIL SYSTEM – UNIQUE CHARACTERS ON WOODEN FLOORS



Natural solutions for healthy floors

Bona's complete range of oils are renewable, made using raw vegetable materials and contain exceptionally low levels of VOC. Their high oil content and minimal solvent content ensures a high degree of saturation with fewer applications, for healthy floors and long-lasting protection.

- ✓ Natural solutions
- ✓ Child safe
- ✓ Waterborne

Bona Nordic Tone

For natural looking whitewashed effects

Bona Nordic Tone is an easy-to-use pre-treatment to Bona Craft Oil, offering numerous possibilities for light and white wood floor effects. Suitable for both softwood and hardwood, it also inhibits yellowing. Bona Nordic Tone can be combined with up to 5% of Bona Mix Colour to change or further intensify the tone.

APPLICATION

When combining Bona Nordic Tone with coloured oils, we recommend sealing the surface with one layer of Bona Hard Wax Oil as a way to simplify maintenance and prevent colour from wearing off. In high traffic areas consider ending with two layers of Hard Wax Oil for increased protection against wear.

KEY BENEFITS

- Fast drying and easy application
- Intensity can be controlled by number of applications
- Waterborne and completely odourless

TECHNICAL DATA

Product base:	Slightly alkaline solution, pigmentation
Dilution:	Do not dilute
Drying time:	Between applications: 1-2 hours* Before oiling: 5-10 hours* <small>*under normal indoor conditions, 20°C/60% R.H. ensure proper ventilation.</small>
Application tools:	Oil application sleeve or wide floor brush
Consumption:	Approx. 8-10 m ² /litre depending on wood type
Cleaning:	Use clean tools with water and soap and dried material can be scrubbed off with water and soap
Safety:	Unclassified
Fire risk:	No
Shelf life:	3 years, from the date of production, in unopened original container
Storage/Transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport
Disposal:	Waste and emptied containers should be handled in accordance with local regulations
Pack sizes:	3 x 5 litres