BONA RICH TONE

Bona Rich Tone

Reactive stain

- For a smoked effect
- Quick drying
- ✓ Odourless

5 L Effect colouring for wooden floors Furbgebung for Holeböden Ecren planc Efforto para coorner suelos de modera Effektrargeing for tragoly

Bona

Dark

Create your own wood story

BONA OIL SYSTEM - UNIQUE CHARACTERS ON WOODEN FLOORS







Natural solutions for healthy floors

Bona's complete range of oils are renewable, made using raw vegetable materials and contain exceptionally low levels of VOC. Their high oil content and minimal solvent content ensures a high degree of saturation with fewer applications, for healthy floors and long-lasting protection.

✓ Natural solutions
✓ Child safe

✓ Waterborne

Bona Rich Tone

Pre-treatment for enhanced richness

Bona Rich Tone is an easy-to-use pre-treatment for oak floors. It creates a rich, dark brown colouration, evocative of smoked oak. Bona Rich Tone can be combined with up to 5% of Bona Mix Colour to change or further intensify the tone.

APPLICATION

Bona Rich Tone is a pre-treatment for indoor wood floor environments. Always seal the surface with Bona Craft Oil and/or Bona Hard Wax Oil directly, depending on the desired colour effect and level of protection needed.

KEY BENEFITS

- Fast drying and easy application
- Waterborne and completely odourless

TECHNICAL DATA

| Product base: | Alkaline solution |
|---------------|--|
| Dilution: | Do not dilute |
| Drying time: | Between applications: 1-2 hours* Before oiling: 5-10 hours* *under normal indoor conditions, 20°C/60% R.H. ensure proper ventilation. |

TECHNICAL DATA (CONTINUED)

| Application tools: | Oil application sleeve |
|--------------------|--|
| Consumption: | Approx. 8-10 m²/litre depending on wood type |
| Cleaning: | Use clean tools with water and soap and dried material can be scrubbed off with water and soap |
| Safety: | Unclassified |
| Fire risk: | No |
| Shelf life: | 3 years, from the date of production, in unopened original container |
| Storage/Transport: | The temperature must not fall below +5°C or exceed +25°C during storage and transport |
| Disposal: | Waste and emptied containers should be handled in accordance with local regulations |
| Pack sizes: | 3 x 5 litres |

