

Bona SuperSport Primer

BONA SUPERSPORT SYSTEM - GREAT SURFACES FOR GREAT GAMES









Bona SuperSport Primer

Great surfaces for great games

1-component waterborne primer for untreated wood sports floors. Excellent adhesion to wood and side-bonding reducing properties creates an optimal foundation for further treatment and line-marking. Made from a polyurethane dispersion consisting of 70% renewable raw materials, being easy to abrade and apply.

APPLICATION

Apply an even coat of Bona SuperSport Primer using a Bona Applicator Bar or a Bona Roller. Care should be taken to achieve a uniform level of timber saturation to avoid timber colour variation. Always maintain a 'wet edge' to avoid overlaps. Allow to dry and continue with Bona SuperSport ONE or SuperSport HD and line-marking paint according to the recommended treatment schedule. If Bona SuperSport Primer has been allowed more than 24 hours drying time then an intermediate sanding is always required before applying further coats.

KEY BENEFITS

- · Reduced risk of side-bonding
- Medium-rich wood colouration
- Excellent abrasion properties

TECHNICAL DATA

Type of lacquer: Waterborne 1-component

polyurethane dispersion

TECHNICAL DATA (continued)

Solids content: Approx 32% VOC: Max 60q/litre

Dilution: If required, dilute with Bona Retarder (4%) for

longer open time.

Drying time: 2-3 hours at 20°C/60° R.H.

Application tools: Bona Applicator Bar or Bona Roller 8-10 m²/litre (120-100g/m²) per coat Application rate:

Safety: Unclassified

Wipe tools free from residual material before Cleaning:

cleaning with a minimal amount of water. Dried

material can be removed with acetone.

Shelf life: 1 year from date of production in

unopened original container.

Storage/transport: The temperature must not fall below +5°C or

exceed +25°C during storage and transport.

Disposal: Wastes and emptied containers should be

handled in accordance with local regulations.

Pack sizes: 2 x 10 litres (24 boxes per pallet)

