

ULTRA
MATT
SURFACES



RAW EXPERIENCE, TRUE PROTECTION

Bona Traffic HD Raw – Creating ultra matt floors with great durability



Bona Traffic HD Raw

Raw experience, True protection

Bona Traffic HD Raw brings a uniquely true wood experience into the world of lacquered floors. Offering an ultra matt floor surface with a high level of protection, Bona Traffic HD Raw creates a soft haptic feeling of untreated wood when touching the floor.

A pleasure to walk on with high slip safety makes Bona Traffic HD Raw great for homes with both children and pets, as well as commercial floor surfaces. Bona Traffic HD Raw - the raw experience of wood, protected.

APPLICATION

Bona Traffic HD Raw offers a high level of protection for wooden floors while maintaining the look and feel of untreated wood. A premium product for a premium look.

KEY BENEFITS

- Ultra matt floor in all angles
- High wear resistance
- Soft haptic feeling
- Great scuff mark and chemical resistance
- Easy to apply & abrade
- Low odour
- High slip resistance
- EC1 Plus compliant

TECHNICAL DATA

Product base:	2-component waterborne polyurethane topcoat.
Solids content:	Approx. ~32%.
Sheen at 60° & 85°:	Approx. 4% = Ultra Matt.
Mixing ratio:	1 part Hardener to 1 litre Traffic HD Raw or 0.41 L. Hardener to 4.54 L Traffic HD Raw (≈8 vol%).
Pot Life:	Max. 3 hours at 20°C (shorter if warmer).
Drying time:	Full curing: 7 days* Light use: 24 hours* <small>*under normal climate conditions, 20°C/60% R.H.</small>
Dilution:	If required, dilute with 4% Bona Retarder for a longer open time.
Cleaning:	Wipe tools free from residual material before cleaning with a minimum of water. Dried material can be removed with acetone.
Shelf life:	1 year from date of production in unopened original container.
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport.
Sizes:	3 x 4.95 litres incl. hardener.